

Settings

Based on v1.6.9 of blogr-docs plugin

Blogr Docs Settings

The docs settings page is available at `/admin/docs-settings` (or your custom admin path). Settings are persisted to `config/blogr-docs.php`.

General

Field	Config key	Default	Description
Enabled	<code>enabled</code>	<code>true</code>	Enable or disable the documentation system. When disabled, all doc routes return 404.
Prefix	<code>prefix</code>	<code>docs</code>	URL prefix for all documentation routes (e.g. <code>/docs</code> , <code>/help</code> , <code>/manual</code>).
Middleware	<code>middleware</code>	<code>['web']</code>	Middleware applied to frontend documentation routes.

Sidebar

Configure the documentation navigation tree in the left sidebar.

Field	Config key	Default	Description
-------	------------	---------	-------------

Collapsible	<code>sidebar.collapsible</code>	<code>true</code>	Allow collapsing/expanding parent article groups.
Max depth	<code>sidebar.max_depth</code>	<code>5</code>	Maximum nesting level displayed in the sidebar tree.
Show icons	<code>sidebar.show_icons</code>	<code>true</code>	Display hero icons next to article titles in the sidebar.

Table of Contents (TOC)

Configure the "On this page" sidebar on the right of each article.

Field	Config key	Default	Description
Enabled	<code>toc.enabled</code>	<code>true</code>	Enable the table of contents sidebar. Also controls heading ID injection (anchor links).
Max level	<code>toc.max_level</code>	<code>3</code>	Maximum heading level displayed in the TOC (<code>2</code> = h2 only, <code>3</code> = h2 + h3).

The TOC is generated from `<h2>` and `<h3>` tags in the article content. Each heading gets an `id` attribute for anchor linking. The TOC sidebar is visible on screens $\geq 1024\text{px}$ (`lg:block`).

Individual articles can override the global TOC setting via the `Display table of contents` toggle in the article edit form.

Search

Server-side search across article titles, content, excerpts, and slugs.

Field	Config key	Default	Description
Enabled	<code>search.enabled</code>	<code>true</code>	Show the search field in the sidebar.
Min length	<code>search.min_length</code>	<code>2</code>	Minimum query length to trigger a search.
Max results	<code>search.max_results</code>	<code>20</code>	Maximum number of search results to return.

Search queries are submitted via `?q=` query parameter to the docs index page. Results are rendered from the `search.blade.php` view.

PDF Export

Happytodev

Generate PDF downloads of any documentation article.

Field	Config key	Default	Description
Enabled	<code>pdf.enabled</code>	<code>false</code>	Show the "Download PDF" button on article pages.
Driver	<code>pdf.driver</code>	<code>dompdf</code>	PDF rendering engine (currently only <code>dompdf</code> supported).
Page size	<code>pdf.page_size</code>	<code>A4</code>	Paper size (A4, Letter, Legal, A3, A5).
Orientation	<code>pdf.orientation</code>	<code>portrait</code>	Page orientation (Portrait / Landscape).

PDF Watermark

Add a text or image watermark to PDF exports.

Field	Config key	Default	Description
Enabled	<code>pdf.watermark.enabled</code>	<code>false</code>	Activate watermark on PDF exports.
Text	<code>pdf.watermark.text</code>	<code>Confidential</code>	Watermark text. Rendered only if no image is provided. Both text and image can be displayed together.
Image	<code>pdf.watermark.image</code>	<code>null</code>	Upload a watermark image. Stored in <code>storage/app/public/docs/pdf-watermarks/</code> .
Opacity	<code>pdf.watermark.opacity</code>	<code>0.2</code>	Watermark opacity (0.1 to 1.0).
Position	<code>pdf.watermark.position</code>	<code>center</code>	Watermark position on the page: <code>center</code> , <code>top-left</code> , <code>top-center</code> , <code>top-right</code> , <code>center-left</code> , <code>center-right</code> , <code>bottom-left</code> , <code>bottom-center</code> , <code>bottom-right</code> .
Rotation	<code>pdf.watermark.rotation</code>	<code>-45</code>	Rotation angle in degrees (-90 to 90).
Size	<code>pdf.watermark.size</code>	<code>60</code>	Font size in px for text watermarks, max dimension in px for image watermarks.

Embedded Media

Enable or disable embedded media providers in the Markdown converter. These affect how URLs from supported platforms are rendered in article content.

Field	Config key	Default
YouTube	<code>embeds.youtube</code>	<code>true</code>
Vimeo	<code>embeds.vimeo</code>	<code>true</code>
Dailymotion	<code>embeds.dailymotion</code>	<code>true</code>
Spotify	<code>embeds.spotify</code>	<code>true</code>
SoundCloud	<code>embeds.soundcloud</code>	<code>true</code>
Deezer	<code>embeds.deezer</code>	<code>true</code>
Apple Podcasts	<code>embeds.apple_podcasts</code>	<code>true</code>

SEO

Default metadata used when articles don't provide their own.

Field	Config key	Default	Description
Site name	<code>seo.site_name</code>	<code>null</code>	Override the site name for SEO metadata. Falls back to <code>env('APP_NAME')</code> .
Default title	<code>seo.default_title</code>	<code>Documentation</code>	Default <code><title></code> for the docs index page.
Default description	<code>seo.default_description</code>	<code>null</code>	Default meta description for the docs index page.

Config file location

The settings are saved to `config/blogr-docs.php`. The package ships with a default file that is merged during service provider registration. Custom values are written by the settings page via `var_export()`.

To reset to defaults, delete the file and run `php artisan vendor:publish --tag=blogr-docs-config --force`.